



Product number AIS B020

## PRODUCT DATA SHEET

### LINSEED OIL VARNISH

for maximum temperature and pressure resistance

#### Description

**Linseed oil varnish** manufactured by the company A.I. Schulze Chemotechnische Fabrik e.K. is tailored for its use in our main product **BIRKOSIT Dichtungskitt**<sup>®</sup>, a single-component sealing material. It is designed to be mixed with **BIRKOSIT Dichtungskitt**<sup>®</sup> to make it easier to apply. The **linseed oil varnish** is suitable for use in sealants that are subject to the highest quality requirements in terms of their temperature resistance.

#### Service life

When mixed with our product **BIRKOSIT Dichtungskitt**<sup>®</sup>, we guarantee a service life of **10 years** for the **linseed oil varnish**.

#### Application

The **linseed oil varnish** is to be mixed with the product **BIRKOSIT Dichtungskitt**<sup>®</sup> using a putty knife. The mixing ratio is **1 : 10**. (10 parts Birkositt can be mixed with 1 part linseed oil varnish.) The colour is yellow-brown. The product is in a liquid state. The **linseed oil varnish** improves the brushability of the product **BIRKOSIT Dichtungskitt**<sup>®</sup>.

#### Storage

Packed in 1 litre plastic bottles. If stored correctly, the **linseed oil varnish** has a **storage life of 5 years** in the bottle, its properties are stable and it is flexible in its use.

Close the bottle properly if only a part of the contents is going to be used.

Product data sheet as at 02.01.2025. Current download version at [www.a-i-schulze.com](http://www.a-i-schulze.com).