LEINÖLFIRNIS

Product number AIS B020



PRODUCT DATA SHEET

LINSEED OIL VARNISH Description

Linseed oil varnish manufactured by the company A.I. Schulze Chemotechnische Fabrik e.K. is tailored for its use in our main product **BIRKOSIT Dichtungskitt**, a single-component sealing material. It is designed to be mixed with **BIRKOSIT Dichtungskitt** to make it easier to apply. The **linseed oil varnish** is suitable for use in sealants that are subject to the highest quality requirements in terms of their temperature resistance.

LINSEED OIL VARNISH Service life

When mixed with our product **BIRKOSIT** Dichtungskitt[®], we guarantee a service life **of 10 years** for the **linseed oil varnish**.

LINSEED OIL VARNISH Application

The **linseed oil varnish** is to be mixed with the product **BIRKOSIT Dichtungskitt** using a putty knife. The mixing ratio is **1 : 10**. (10 parts Birkosit can be mixed with 1 part linseed oil varnish.) The colour is yellow-brown. The product is in a liquid state. The **linseed oil varnish** improves the brushability of the product **BIRKOSIT Dichtungskitt**.

LINSEED OIL VARNISH Storage

Packed in 1 litre plastic bottles. If stored correctly, the **linseed oil varnish** has a **storage life of 5 years** in the bottle, its properties are stable and it is flexible in its use. Close the bottle properly if only a part of the contents is going to be used. Product data sheet as of 01.05.2012. <u>Current download version available at www.a-i-schulze.com.</u>